



Filtertestgerät "Integrity"

Komplettpaket im Tragekoffer

SPECIFICATION

- user languages:
Italian, English, German, French, Spanish and Portuguese
- pressure measure range 0-4,000 mbar
- absolute measurement accuracy of 20 mbar
- measuring accuracy 0.2% relative FSS
- overpressure proof up to 5,000 mbar
- semiautomatic pressure hold test
- 1 to 19 free programmable sets of test parameters
- up to 150 test protocols stored, then first in first out
- memory full indication
- battery monitoring
- permanent data retention
- independent switching off
- charging time typically 3 hours
- running time typically 10 hours
- connector on filter tester is Rectus 5mm male stainless steel standard-type
- USB-mini (B) connector
- housing material, ABS
- protection class IP 54
- ambient temperature for operation 3 - 50°C
- data backup and device programming with WinFilter 3.0-software
- printout with optional mobile printer
- suitcase with foam inlay
- International charger 100 - 240V 47-63Hz, EU-, UK-, US-, AU-Plugs
- USB transfer cable
- CE certified

Package includes:

- | | |
|-------------------|--|
| 1 x N° FS1_0030 | Filtertester FS1 |
| 1 x N° FS1_0104 | Power charger and Power adaptors: EU, US, UK, AU |
| 1 x N° FS1_0035 | USB stick with WinFilter PC-software |
| 1 x N° 3EL11014 | USB/USB-mini cord |
| 1 x N° FS1_0008 | Plastic case |
| 1 x N° DAF-040538 | Calibration certificate |

Accessories:

- | | |
|---------------|--|
| - N° FS1_0053 | Printer functionality for Filtertester FS1 |
| - N° FS1_0052 | Mobile Printer, wireless |