



Filtertestgerät "Integrity" - international

Fully automatic integrity testing device:

- Languages integrated: German, English, French, Spanish, Italian, Portuguese,
- For integrity tests with filter upstream volumes from 0.025 up to 999 litres,
- Pressure measure range 0-4500 mbar,
- overpressure proof 8000mbar,
- Abs. deviation for pressure measuring max 0.2% (ref. tot. range),
- Stainless steel pressure connectors,
- Connector for supply air is Stäubli male RBE03,
- Connector for filter is Stäubli female RBE03,
- Automatic adjustment of test pressure,
- Automatic execution of pressure hold test,
- Automatic venting of the filter housing after the test,
- Built-in thermal strip printer for documentation, 57mm paper width,
- Data backup and data handling on PC with included WinFilter software,
- Up to 19 different test routines can be created,
- Up to 200 test protocols stored in a first-in-first-out-memory,
- Memory full indication,
- Graphic display,
- Battery operation possible for up to 8 hours,
- **Not restricted as per special provision A123**
- Temperature range for operating 0...40°C,
- Housing with keypad, made of ABS (UL94HB) and polycarbonate,
- Keypad design LiquoSystems neutral
- Dimensions ca. 300x250x130 mm,
- Protection class IP53
- Power supply unit 100..240V AC,
- Mains adapters for Europe, UK, the USA and Australia
- **WinFilter** software on USB stick,
- USB data transfer cable
- Calibration certificate, endurance test certificate
- operating instructions
- including carrying bag, black, uni
- including transport case, black, elements light gray
- packaging included

Including the following accessories:

4 x Printer paper roll, item no.: FS3_0007

1 x outlet tubing:

- Length 3 meters
- Hose 8/6mm, type FESTO, material PUR, blue
- Side 1: Rectus plug-in nipple with plastic hose connection
- Side 2: without connection
- incl. leak test

1 x inlet tubing:

- Length 3 meters
- Hose 8/6mm, type FESTO, material PUR, red
- Side 1: Rectus coupling with plastic hose connection
- Side 2: without connection
- incl. leak test

Optionally available:

- printer cover hood for IP54, item no.: FS3_0009
- external valve for venting, item no.: FS3_0008